




Photo	Product	MOQ(pcs.)
	sonoff wifi Refit ( Do not include 433 control fuction ) Power Supply: 90V~250V AC Max. Current: 10A Wireless Standard: Wi-Fi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: 5%-95% Material: ABS Connector: universal Weight: 51g	50
		200
		1000
	sonoff RF wifi Refit ( Include 433 control fuction ) Power Supply: 90V~250V AC Max. Current: 10A Wireless Standard: Wi-Fi 2.4GHz b/g/n & 433MHz Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: 5%-90% Material: ABS V0 Connector: Universal Weight: 53g	1-59
		60-100
		500
	slampher RF ( Include 433 control fuction ) Power Supply: 90V~250V AC Max. Current: 2A Wireless Standard: Wi-Fi 2.4GHz b/g/n & 433MHz Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: ≤80% Material: FR-ABS Connector: universal Weight: 86g	10
		50pcs
		1000+
 <p>433MHz 无线遥控器 可控制四路开关</p>	433MHz Remove control 4pcs button 4 Buttons Frequency: 433MHz 40g	1-100
		101-500
		500+
	Sonoff TH10 Temperature Humidity control Refit 10A Power Supply: 90V~250V AC Max. Current: 10A /16A Wireless Standard: WiFi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: 5%-95% Material: FR-ABS Connector: universal CE & RoHS Certified Weight 84g	1-49
		50-300
		300+








Photo	Product	MOQ(pcs.)
	Sonoff TH16 Temperature Humidity control Refit 16A Power Supply: 90V~250V AC Max. Current: 10A /16A Wireless Standard: WiFi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: 5%-95% Material: FR-ABS Connector: universal CE & RoHS Certified Weight 84g	1-49
		50-300
		300+
 线长0.5米 不防水温湿度传感器	Sonoff sensor NOT WATERPROOF Temperature: -40°C~+80°C Humidity Measuring Range: 0~99.9%RH Accuracy: in 25°C Temperature: ±0.5%RH Humidity: ±3%RH(10...90%RH) Power supply: 3.3-5.2V DC(5V recommended) Sensor Type Temperature: resistive sensor Humidity: capacitive sensor Weight :22 g	50-149
		150-299
		300+
 线长1米 防水温度探头	Sonoff sensor WATERPROOF ,Length=1 M Weight :26g Measuring Temperature: -55°C~+125°C Power Supply: 3.0-5.5V Stainless steel temperature probe	50-149
		150-299
		300+
		1000+
	Sonoff POW Energy profiler 16A Power Supply: 90V~250V AC Max. Current: 16A Power: 3500W Wireless Standard: Wi-Fi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating temp: 0 °C ~ 40 °C (32°F ~ 104°F) Operating Humidity: 5%~90%RH, Non-condensing Material: FR-ABS Connector: Universal CE & RoHS Certified Weight: 87g	1-50
		51-300
		300+
	Sonoff DUAL Refit 10A Power Supply: 90V~250V AC Max. Current: 16A Wireless Standard: Wi-Fi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: 5%-95% Material: FR-ABS Connector: universal CE & RoHS Certified Weight: 87g	1-50
		51-300
		300+





Photo	Product	MOQ(pcs.)
	sonoff touch EU Power Supply: 90V~250V AC Max. Current: 2A Wireless Standard: Wi-Fi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: 5%-95% Material: ABS+Toughened glass panel Connector: universal Weight: 116g	20-199
		200-499
		500+
	sonoff touch US Power Supply: 90V~250V AC Max. Current: 2A Wireless Standard: Wi-Fi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: 5%-95% Material: ABS+Toughened glass panel Connector: universal Weight: 150g	20-199
		200-499
		500+








Photo	Product	MOQ(pcs.)
	Sonoff 4CH Power Supply: 90~250V AC Rated frequency: 50HZ/60HZ Max current: 10A Max Power: 2200W Wireless Standard: Wi-Fi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating temp: 0 °C ~ 40 °C (32°F ~ 104°F) Operating Humidity: 5%~90%RH, Non-condensing Weight: 220g	50-149
		150-299
		300+
	Sonoff 4CH pro Working modes: inching/interlock/self-locking mode Adjustable time for inching mode: 0.25-4s Power Supply: 90-250V AC(50/60Hz) / 5-24V DC Max current: 10A/gang Max Power: 2200W/gang Wireless Standard: Wi-Fi 2.4GHz b/g/n, 433MHz RF Security Mechanism: WEP/WPA-PSK/WPA2-PSK Weight:235g	1-50
		51-300
		300+
	sonoff T1 uk 1c Power Supply: 90~250V AC Rated frequency: 50HZ/60HZ Max. Current: 2A/250V/gang Max. Power: 600W/gang Dimension: 86mm*86mm (UK Standard) Control Methods: Touch/App eWeLink/RF Remote Wireless Standard: WiFi 2.4GHz & 433MHz RF Material: ABS V0+ Toughened Glass Panel Security Mechanism: WEP/WPA-PSK/WPA2-PSK Weight: 130g	1-50
		51-300
		300+
	sonoff T1 uk 2C Power Supply: 90~250V AC Rated frequency: 50HZ/60HZ Max. Current: 2A/250V/gang Max. Power: 600W/gang Dimension: 86mm*86mm (UK Standard) Control Methods: Touch/App eWeLink/RF Remote Wireless Standard: WiFi 2.4GHz & 433MHz RF Material: ABS V0+ Toughened Glass Panel Security Mechanism: WEP/WPA-PSK/WPA2-PSK Weight: 130g	1-50
		51-300
		300+
	sonoff T1 uk 3C Power Supply: 90~250V AC Rated frequency: 50HZ/60HZ Max. Current: 2A/250V/gang Max. Power: 600W/gang Dimension: 86mm*86mm (UK Standard) Control Methods: Touch/App eWeLink/RF Remote Wireless Standard: WiFi 2.4GHz & 433MHz RF Material: ABS V0+ Toughened Glass Panel Security Mechanism: WEP/WPA-PSK/WPA2-PSK Weight: 130g	1-50
		51-300
		300+








Photo	Product	MOQ(pcs.)
	sonoff B1 Lamp Base: E27 Rated Power: 6W Typical Lumen Output: 600lm Beam Angle: 120 Degree typical Color Temperature: 2800K-6500K & RGB full color Dimmable: Yes (via app/Amazon Echo/Google Home) Wireless Standard: WiFi 2.4GHz Rated Input Voltage: 90-260V AC 50/60Hz Stand-by (Light off) power: 0.5W Max Operating temp: 0 °C ~ 40 °C (32°F ~ 104°F) Operating Humidity: 5%~90%RH, Non-condensing Weight:165g	1-50
		51-300
		300+
	sonoff RF bridge New version Power Supply: Micro USB 5V Supported Radio: 433MHz RF Supports fixed code 433 frequency: PT2260, PT2262, PT2264, EV1527, etc. Not support to learn rolling code and dynamic code Wireless Standard: WiFi 2.4GHz Dimension: 62*62*20(mm) Weight :35g	1-50
		51-300
		300+
	sonoff waterproof case Weight: 150G	1-50
		51-300
		300+
	broadlink wifi smart socket MINI3 Power Supply: 90V~250V AC Max. Current: 10A Wireless Standard: Wi-Fi 2.4GHz b/g/n Security Mechanism: WEP/WPA-PSK/WPA2-PSK Operating Temp.: 0°C~40°C Operating Humidity: ≤80% Material: FR-ABS Certification: CE/RoHS/FCC	1-50
		51-300
		300+
	broadlink wiFi box fa1	1-50
		51-300
		300+





Photo	Product	MOQ(pcs.)
	RM mini3	1
	RM PRO	1 5 10
	T1 EU 1C Power Supply: 90~250V AC Rated frequency: 50HZ/60HZ Max. Current: 2A/250V/gang Max. Power: 600W/gang Dimension: 120mm*78mm (US Standard) Control Methods: Touch/App eWeLink/RF Remote Wireless Standard: WiFi 2.4GHz & 315MHz RF Material: ABS V0+ Toughened Glass Panel Security Mechanism: WEP/WPA-PSK/WPA2-PSK Certification: CE, RoHS	1-50 51-300 300+
	T1 EU 2C Power Supply: 90~250V AC Rated frequency: 50HZ/60HZ Max. Current: 2A/250V/gang Max. Power: 600W/gang Dimension: 120mm*78mm (US Standard) Control Methods: Touch/App eWeLink/RF Remote Wireless Standard: WiFi 2.4GHz & 315MHz RF Material: ABS V0+ Toughened Glass Panel Security Mechanism: WEP/WPA-PSK/WPA2-PSK Certification: CE, RoHS	1-50 51-300 300+
	s31 Plug Standard: US Max. Current: 16A Max. Power: 4200w Voltage Input: 90~264V AC, 50/60HZ Output power: 802.11b:16±2dBm; 802.11g:13±2dBm Receive sensitivity: 802.11b: <-84dBm(11Mbps); 802.11g: <-68dBm(54Mbps) Wireless Standard: WiFi 2.4GHz Encryption: AES/TKIP Operating temp: 0 °C ~ 40 °C (32°F ~ 104°F) Operating Humidity: 5%~90%RH, Non-condensing Dimensions: 75.7x39.7x32mm Weight: 135g	10-99 100-299 300+



Photo	Product	MOQ(pcs.)
	4ch ProR2 Working modes: inching/interlock/self-locking mode Adjustable time for inching mode: 0.25-4s Power Supply: 90-250V AC(50/60Hz) / 5-24V DC Max current: 10A/gang Max Power: 2200W/gang Wireless Standard: Wi-Fi 2.4GHz b/g/n, 433MHz RF Security Mechanism: WEP/WPA-PSK/WPA2-PSK Weight:127g	10-99
		100-299
		300+
	4CHR2 Weight: 128g	10-99
		100-299
		300+
	S20 EU wifi smart socket Type F Weight: 216g	50-149
		150-299
		300+
	S20 EU wifi smart socket Type E Weight: 216g	50-149
		150-299
		300+
	Model: 4ch Weight: 200g Wifi: 2.4GHz 802.11b/g/n self-locking Input/: AC 90-264V 50/60Hz Max load 250V. 10A 2200W/Gang 250V. 16A 3500W/Letal	50
		150
		300+